



THIRD FLOOR FRAMING PLAN  
SCALE 1:100

NOTES

- \* ALL DIMENSIONS ARE IN MILLIMETERS. LEVELS ARE IN METERS, UNLESS STATED OTHERWISE. DRAWING SHOULD NOT BE SCALED. FOLLOW WRITTEN DIMENSIONS ONLY.
- \* THIS DRAWING IS TO BE READ WITH RELEVANT ARCH, STRU, MECH, & ELEC. DRAWINGS.
- \* SOIL BEARING CAPACITY IS ASSUMED TO BE 300 KN/m<sup>2</sup>. THE CONTRACTOR SHALL VERIFY THE ACTUAL SOIL BEARING CAPACITY BEFORE PROCEEDING WITH THE WORKS.
- \* ALL BLINDING CONCRETE SHALL HAVE A MINIMUM CRUSHING STRENGTH OF 15N/mm<sup>2</sup>.
- \* ALL REINFORCED CONCRETE SHALL HAVE A MINIMUM CRUSHING STRENGTH OF 30N/mm<sup>2</sup> USING ORDINARY PORTLAND CEMENT AND 20mm MAXIMUM SIZE AGGREGATE.
- \* BLOCK WORK SHALL HAVE A MINIMUM CRUSHING STRENGTH OF 7N/mm<sup>2</sup>.
- \* REINFORCEMENT COVER FOR REINF. CONCRETE BELOW AND ABOVE GROUND:
  - ABOVE GROUND : 65mm
  - BELOW AND ABOVE GROUND:
    - COLUMNS: 25mm (INTERNAL)
    - BEAMS : 25mm (INTERNAL)
    - BEAMS : 40mm (EXTERNAL)
    - SLABS : 20mm

REV.	DESCRIPTION	BY	DATE

ENGINEERS COMMENTS / APPROVAL

CONSULTANT  
Grid Design Solutions P.L.Ltd  
Techno Park, Thiruvananthapuram,  
Kerala, India-695023  
Tel : +91471272797  
Fax : +91471272797

SUB CONTRACTOR  
OWNER  
LOCATION: -----  
DISCIPLINE: STRUCTURAL  
PROJECT: -----

THIRD FLOOR SLAB  
FRAMING PLAN

SCALE	CHECKED	K.C
M.P	FRGL NO.	
DRWN	DRG. NO.	
DESIGNED	IRU	